

MB OFFICE Linear Curve



INDOOR SERIES



PRODUCT OVERVIEW

The **AL TSA Office Linear Curve** is the ideal luminaire for interior designers and architects, offering both creativity and style. This luminaire is constructed from a premium grade aluminium profile, and a PMMA clip-in diffuser system.

The **AL TSA Office Linear Curve** can be surface mounted, suspended or recessed. This luminaire can be customized to any form or shape according to the specific needs of the application.

Quality comes standard...



Hours
LIFESPAN



IP42
Indoor



Low
MAINTENANCE



Year
WARRANTY



Product
CERTIFICATION

APPLICATIONS		FEATURES
Hotels	Conference/Meeting Rooms	Polycarbonate Lens
Factories & Offices	Commercial Applications	Beam Angle 120°
Schools	Colleges	No UV or IR
Universities	Hospitals	Easy Installation
Book Shops	Entertainment Spaces	5 Year Warranty
CONSTRUCTION DETAILS		
Silver/White/Black Housing Finish	Aluminium Housing	
IP42 Ingress Protection	PC	

Office Linear Curve

TECHNICAL DATA

Supply Voltage	110-240VAC
Power Consumption	50W/m
Efficacy	130lm/W (Delivered)
Profile Colour	White/Black/Silver/Gold
Colour Temperature	3000K,4000K,6000K, RGB
Dimensions	51mm(w) X 75mm (h)
Weight	2.2kg/m



MECHANICAL DATA

Humidity Range:	30-60%
LED Brand:	Hongli 2835
Size:	51mmx75mm
Operating Temperature:	-20°C ~ 50°C
Housing Material:	Aluminium Housing
Lens Material:	PC
Housing Finish:	Silver/White/Black
IP Rating	IP42
Mounting Configuration:	Recessed/Surface
Glare Rating:	UGR 22
Flicker&DLC Specification:	SVM<0.4 DLC V4.0

ELECTRICAL DATA

FEATURES		
Driver:	Greenbo	EMC Applicable
Electrical Class:	Class 1	Triac Dimmable
Nominal Voltage Range:	184 - 265 VAC	Tridonic Optional
Power Factor:	>0.90	Vossloh Optional
THD:	20%	
Surge Protection:	Standard 1000V- Optional 2750V	
Battery Backup:	20% 30 - 90 Minutes	
Cable Entry:	Bottom	

Office Linear Curve

INSTALLATION EXAMPLES

