

AL TSA Beta Batten



INDOOR SERIES



PRODUCT OVERVIEW

The **AL TSA Beta Batten** is a premier linear, linkable light solution for any personal or workspace.

With its high-tech optical design and full aluminium housing, the **AL TSA Beta Batten** does not only provide a functional lighting solution but is also classy and graceful.

The **AL TSA Beta Batten** can be linked in an array with optional motion sensors which can provide bi-level dimming and control, while energy and maintenance costs can be dramatically reduced.

Constructed with an aluminium alloy body that provides excellent heat dissipation and a polycarbonate lens to provide superior illumination while limiting glare, the **AL TSA Beta Batten** is one of the most effective choices for a wide range of applications.

Quality comes standard...



Hours
LIFESPAN



Durable
DESIGN



IP65
Indoor



Low
MAINTENANCE



Year
WARRANTY



Product
CERTIFICATION

APPLICATIONS

Warehouses

Offices

Factories

Supermarkets

Parking Areas

Workshops

CONSTRUCTION DETAILS

IK08 Impact Resistance

IP65 Ingress Protection

Aluminium Housing

Silver Housing Finish

PC Lens

FEATURES

Linear design

High Luminous Efficiency

Excellent heat dissipation

Warranty: 5 Years

CRI: 80

Input Voltage: 180-265VAC

Beta Batten

TECHNICAL DATA | Indoor

MODEL No.:	VOLTAGE (V)	POWER (W)	LUMEN (lm/W)	LENGTH (mm)	BEAM ANGLE	CRI	CCT (K)	SIZE
MB/B/2FT/20	100-265	20	100	600x84x46	140°	>80	3000-6000	2FT
MB/B/4FT/20	100-265	20	100	1200x84x46	140°	>80	3000-6000	4FT
MB/B/4FT/40	100-265	40	100	1200x84x46	140°	>80	3000-6000	4FT
MB/B/4FT/60	100-265	60	100	1200x84x46	140°	>80	3000-6000	4FT
MB/B/5FT/25	100-265	25	100	1500x84x46	140°	>80	3000-6000	5FT
MB/B/5FT/40	100-265	40	100	1500x84x46	140°	>80	3000-6000	5FT
MB/B/5FT/60	100-265	60	100	1500x84x46	140°	>80	3000-6000	5FT
MB/B/5FT/80	100-265	80	100	1500x84x46	140°	>80	3000-6000	5FT

* **Lumen Output:** 100lm/W (100) / 120lm/W (120)

** **Colour Temperature:** 2000-3000K (02) / 4000K (04) / 6000K (06)

MECHANICAL DATA

Lamp Description:	Hongli 2835		
Cut Out Sizes:	600x84x46	1200x84x46	1500x84x46
Operating Temperature:	-20°C ~ 50°C		
Housing Material:	Aluminium		
Lens Material:	PC		
Housing Finish:	Silver		
IP Rating:	IP65		
Mounting Configuration:	Surface/Suspended		

ELECTRICAL DATA

FEATURES		
Driver:	Zhengyuan	EMC Applicable
Electrical Class:	Class 1	Triac Dimmable
Nominal Voltage Range:	184 - 264 VAC	DALI Control
Power Factor:	>0.95	1-10V Control
THD:	12%	Motion Sensor
Surge Protection:	Standard 1000V- Optional 2750V	
Battery Backup:	20% 30 - 90 Minutes	
Photocell:	External	
Cable Entry:	Side	

Beta Batten

PHOTOMETRIC DATA

